Safety

Catalog No.

1120

RF Meter

The **TESCO RF Meter** combines all the features needed for fast, accurate measurements of electromagnetic fields. This instrument was designed to measure RF, but also has the ability to measure electric and magnetic fields.

The RF (Radio/Microwave) setting can detect up to three billion Hz (3 GHz), which lets you gauge radio-wave power, cellular phone equipment, microwave and many types of RF emitting household and industrial equipment. The RF setting detects vertical electric fields parallel to the long axis of the meter. The RF Meter's primary use is to detect ON-AIR status of transmitters (or to detect concealed transmitters), to check AMI meters, microwave ovens or other microwave equipment for leakage, and to look for RFI sources.

The Radio/Microwave section has a small L-shaped antenna in the front. The signal is amplified and converted to a power density magnitude, calibrated at typical home microwave oven frequency (2 GHz). The RF Meter reads 0 to 1 milliwatt/square centimeter. The resolution at the bottom of the range is 0.01 mW/cm2. A radio wave strength of 0.01 mW/cm2 has 0.006 KV/m and 0.2 milligauss, respectively, of electric and magnetic field (RMS averaged), while a strength of 1 mW/cm2 corresponds to 0.06 KV/m and 2 milligauss. Typical accuracy is within a factor of two. Variations may be caused by reflections off the user's hand and body.





TESCO METERING



Safety

Catalog No.

1120

RF Meter

Specifications

Frequency Range:

50 MHz-3000 MHz (3 GHz)

Range Resolution:

• 1 mW/cm2 / 0.01 mW/cm2

Accuracy:

0.5x to 2x of reading

Settings

- A: Magnetic Field (0-100 milligauss range)
- B: Magnetic Field (O-3 milligauss range)
- C: Electric Field
- RF: Radio/microwave (mW/cm2)

Dimensions:

• 5.0 x 2.6 x 2.4 in (129 x 67 x 62 mm)

Weight:

• 8 oz

Battery:

• 9 Volt alkaline (40 hour life) / Low Battery Indicator





TESCO METERING

